

# Industrial Temperature microSD UHS-I

[kingston.com/flash](http://kingston.com/flash)

## Ideal for industrial applications and extreme conditions.

Kingston's Industrial Temperature microSD UHS-I has an operating temperature rating of -40°C to 85°C, making it suitable for harsh environments. Its high operating temperature rating means it stands up to extreme heat in the desert and in test and measurement situations where standard microSD cards may fail, while its low operating temperature rating allows for use in below freezing weather, where equipment may be left outside for extended periods of time. Its high insertion rating is ideal for applications in which the card will be frequently accessed and removed from host devices, and its MLC NAND allows for large amounts of data to be written to the card.

Kingston® tests these cards extensively during pre-production and new build qualifications. Cards must pass thermal cycle testing, with interval testing at various extreme temperatures; vigorous temperature humidity bias, comprised of several hundred hours of testing to ensure durability at different humidity levels; and wide temp chamber testing. In addition, these cards are tested to be waterproof<sup>1</sup>, temperature proof<sup>2</sup>, shock/vibration proof<sup>3</sup> and X-ray proof<sup>4</sup>. So you can rest assured that your photos, videos and other important files will be protected.

With UHS-I Speed Class U1 speeds of up to 90MB/s read and 45MB/s write, the card is ideal for applications requiring greater bandwidth when recording large datasets. Higher sustained write speeds ensure data integrity by reducing transmission stutter, and the card also offers faster upload times when transferring files to a PC. The smallest available SD card, it is the standard expandable storage option for many GPS, tablets, smartphones and industrial devices and, with the included adapter, can be used in standard-size SDHC/SDXC host devices.

- › Speed may vary due to host and device configuration
- › Extensively tested for industrial applications
- › UHS-I Speed Class U1
- › Small form factor



Waterproof<sup>1</sup>



Temperature proof<sup>2</sup>



Shock and vibration proof<sup>3</sup>



Protected from airport X-rays<sup>4</sup>

Features/specs on reverse >>



# Industrial Temperature microSD UHS-I

## FEATURES/BENEFITS

- > **Industrial-grade features** — The card's operating temperature rating of -40°C to 85°C makes it perfect for harsh environments. For durability, it's rated for 10,000 minimum insertions.
- > **Tested for industrial applications** — Kingston uses wide and broad temperature testing so you can feel secure using the card in industrial applications.
- > **UHS-I interface** — Its UHS-I interface offers higher sustained write speeds to ensure data integrity by reducing transmission stutter.
- > **MLC NAND** — MLC NAND allows for large amounts of data to be written to the card.

## SPECIFICATIONS

- > **Capacities**<sup>5</sup> 8GB, 16GB, 32GB
- > **Performance**<sup>6</sup> UHS-I Speed Class 1 (U1)
  - 8GB: 90MB/s read and 20MB/s write,
  - 16GB-32GB: 90MB/s read and 45MB/s write
- > **microSD Dimensions** 11mm x 15mm x 1mm
- > **SD Adapter Dimensions** 24mm x 32mm x 2.1mm
- > **Format** FAT32 (microSDHC 8GB-32GB)
- > **Operating & Storage Temperature** -40°C to 85°C
- > **Voltage** 3.3V
- > **Thermal Cycle Testing** interval testing completed at various extreme temperatures
- > **Vigorous Temperature Humidity Bias** several hundred hours of testing to ensure durability at varying levels of humidity
- > **Wide Temp Chamber Testing** completed on all SDCIT cards prior to production
- > **Warranty**<sup>7</sup> 5 years



## PART NUMBERS

SDCIT/8GB  
SDCIT/16GB  
SDCIT/32GB

## Card only (SD adapter not included):

SDCIT/8GBSP  
SDCIT/16GBSP  
SDCIT/32GBSP

## OPTIONAL ACCESSORIES

FCR-MLG4 – MobileLite G4, USB 3.0 Card Reader  
FCR-HS4 – USB 3.0 All-in-One Media Reader

1 IEC/EN 60529 IPX7 certified for protection against continuous water submersion for up to 30 min. and a depth of up to 1m.

2 Withstands temperatures ranging from -40 °C to 85 °C.

3 Based on MIL-STD-883H, METHOD 2002.5 military standard test method.

4 Protected against X-ray exposure based on ISO7816-1 guidelines.

5 Some of the listed capacity on a Flash storage device is used for formatting and other functions and is thus not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash Guide at [kingston.com/flashguide](http://kingston.com/flashguide).

6 Speed may vary due to host and device configuration.

7 Kingston Flash Cards are designed and tested for compatibility with consumer-grade market products. It is recommended that you contact Kingston directly for any OEM opportunities or special use applications that are beyond the standard daily consumer usage. For more information on intended use, please refer to the Flash Memory Guide at [kingston.com/flashguide](http://kingston.com/flashguide).



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2020 Kingston Technology Europe Co LLP and Kingston Digital Europe Co LLP, Kingston Court, Brooklands Close, Sunbury-on-Thames, Middlesex, TW16 7EP, England. Tel: +44 (0) 1932 738888 Fax: +44 (0) 1932 785469 All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-337.3 EN

**Kingston**  
TECHNOLOGY